

Inventflow: Grundfos A-partner

Grundfos TP 50-290/2 A-F-A-BQQE-JX1

Find the pump here:

<https://inventflow.nl/en/pompenfilter/tp/grundfos-tp-50-290-2-a-f-a-bqqe-jx1>

Contact

info@inventflow.nl

+31 (0) 546 45 80 72


Datasheet




Qty.	Description
1	TP 50-290/2 A-F-A-BQQE-JX1  Note! Product picture may differ from actual product Product No.: 96087196 Single-stage centrifugal volute in-line single-head pump: - wear rings made of bronze - cataphoresis treatment - stable sleeve coupling - top-pull-out principle for easy maintenance - optimized hydraulics - in-line design with opposite suction and discharge ports enabling mounting in pipework or on a concrete foundation - corrosion resistant maintenance-free mechanical shaft seal. Phase: The motor is a 3-phase AC motor. Controls: Frequency converter: NONE Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 120 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 2910 rpm Rated flow: 27.4 m³/h Rated head: 24.1 m Actual impeller diameter: 142 mm Code for shaft seal: BQQE Curve tolerance: ISO9906:2012 3B2 Materials: Pump housing: Cast iron EN-GJL-250 ASTM class 35 Impeller: Cast iron EN-GJL-200 ASTM class 30 Installation: Range of ambient temperature: -30 .. 60 °C

Qty.	Description
	Maximum operating pressure: 16 bar Max pressure at stated temp: 16 bar / 120 °C Type of connection: DIN Size of connection: DN 50 Pressure rating for connection: PN 16 Port-to-port length: 340 mm Flange size for motor: FF215 Electrical data: Motor type: 100LC IE Efficiency class: IE3 Rated power - P2: 3 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415D V Rated current: 6.3 A Starting current: 840-920 % Cos phi - power factor: 0.87-0.82 Rated speed: 2900-2920 rpm Efficiency: IE3 87,1% Motor efficiency at full load: 87.1 % Motor efficiency at 3/4 load: 88.0 % Motor efficiency at 1/2 load: 87.7 % Number of poles: 2 Enclosure class (IEC 34-5): 55 Dust/Jetting Insulation class (IEC 85): F Motor No: 87272297 Others: Minimum efficiency index, MEI ≥: 0.70 Net weight: 60.1 kg Gross weight: 72 kg Shipping volume: 0.22 m³ Finnish LVI No.: 4616058 Country of origin: HU Custom tariff no.: 84137051

96087196 TP 50-290/2 A-F-A-BQQE-JX1 50 Hz




Description	Value
General information:	
Product name:	TP 50-290/2 A-F-A-BQQE-JX1
Product No:	96087196
EAN number:	5700395311624
Technical:	
Pump speed on which pump data are based:	2910 rpm
Rated flow:	27.4 m³/h
Rated head:	24.1 m
Maximum head:	290 dm
Actual impeller diameter:	142 mm
Code for shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B2
Pump version:	A
Materials:	
Pump housing:	Cast iron
Pump housing:	EN-GJL-250
Pump housing:	ASTM class 35
Impeller:	Cast iron
Impeller:	EN-GJL-200
Impeller:	ASTM class 30
Material code:	A
Installation:	
Range of ambient temperature:	-30 .. 60 °C
Maximum operating pressure:	16 bar
Max pressure at stated temp:	16 bar / 120 °C
Type of connection:	DIN
Size of connection:	DN 50
Pressure rating for connection:	PN 16
Port-to-port length:	340 mm
Flange size for motor:	FF215
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	100LC
IE Efficiency class:	IE3
Rated power - P2:	3 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415D V
Rated current:	6.3 A
Starting current:	840-920 %
Cos phi - power factor:	0.87-0.82
Rated speed:	2900-2920 rpm
Efficiency:	IE3 87,1%
Motor efficiency at full load:	87.1 %
Motor efficiency at 3/4 load:	88.0 %
Motor efficiency at 1/2 load:	87.7 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	87272297
Controls:	
Frequency converter:	NONE
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	60.1 kg
Gross weight:	72 kg
Shipping volume:	0.22 m³




Description	Value
Finnish LVI No.:	4616058
Country of origin:	HU
Custom tariff no.:	84137051

96087196 TP 50-290/2 A-F-A-BQQE-JX1 50 Hz



96087196 TP 50-290/2 A-F-A-BQQE-JX1 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Spare parts TP 50-290/2, Product No. 96087196
Produced After 1101 (production year and week number)

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
-	Motor			85903837	1	pcs
-	Kit, Ball bearing			96279795	1	
99a	Retaining ring					1
99	Retaining ring					1
111	Ball bearing					1
111	Ball bearing					1
157	O-ring		Diameter: 52			1
			Material type: NBR			
			Thickness: 3			
158	Waved washer					1
-	Kit, end shield			96279831	1	
156a	End shield					1
157	O-ring		Diameter: 52			1
			Material type: NBR			
			Thickness: 3			
158	Waved washer					1
159a	Seal ring					1
-	Kit, fan			96279757	1	
156	Fan					1
159a	Seal ring					1
-	Kit, fan cover			96279826	1	
151b	Label					1
151	Fan cover					1
152	Pan head thread forming screw					4
-	Kit, flange			96279829	1	
156b	Flange					1
159.c	Seal ring					1
-	Kit, key			96279821	1	
171	Parallel key					1
-	Kit, retaining ring			96279799	1	
99	Retaining ring					1
188	Retaining ring					1
-	Kit, shaft seal			96279762	1	
159c	Seal ring					1
159a	Seal ring					1
-	Kit, staybolts			96279832	1	
181	Pan head staybolt					4
-	Kit, terminal board			96279769	1	
	Bracket cpl.					1
163	Hex socket head screw					1
173a	Base					1
173	Pan head thread forming screw		Designation: COMBI TORX T25			1
176	Slot cheese head screw		Designation: COMBI TORX T25			6
			Length (mm): 10			
			Thread: M5			
176	Terminal					1
176	Connecting piece					3
176	Wire clamp					3
176	Terminal board					1
177	Pan head screw					1

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
-	Kit, terminal box			96279771	1	
164	Terminal box cover w/gasket				1	
166	Pan head thread forming screw				4	
1a	Motor stool			98970799	1	pcs
19	Plug			98163028	2	pcs
49	Impeller	Outer diameter: 142		96794864	1	pcs
- 50	Pump housing cpl.			99393253	1	pcs
36	Nut	Thread: M10		96620484	6	
51	Stub shaft			99384155	1	pcs
67	Nut	Thread: M14		92526531	1	pcs
72a	O-ring			92547662	1	pcs
72a	O-ring			92526508	1	pcs
72a	O-ring			97511824	1	pcs
72a	O-ring			99756265	1	pcs
77a	Pan head screw			99266550	4	pcs
105	Shaft seal			99380916	1	pcs
105	Shaft seal			99884645	1	pcs