

Inventflow: Grundfos A-partner

Grundfos CRN 64-5-1 A-F-A-E-HQQE

Find the pump here:

<https://inventflow.nl/en/pompenfilter/crn/grundfos-crn-64-5-1-a-f-a-e-hqqe>

Contact

info@inventflow.nl

+31 (0) 546 45 80 72


Datasheet




Qty.	Description
1	CRN 64-5-1 A-F-A-E-HQQE  Product No.: 96123786 Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation. The pump has the following characteristics: - Impellers, intermediate chambers and outer sleeve are made of Impeller: Stainless steel, EN 1.4401. - Pump head cover and base are made of Pump housing: Stainless steel, EN 1.4408. - The shaft seal has assembly length according to EN 12756. - Power transmission is via cast iron split coupling. Flange standard: - Pipework connection is via DIN flanges/couplings. Phase: The motor is a 3-phase AC motor. Controls: Frequency converter: NONE Liquid: Pumped liquid: Water Liquid temperature range: -40 .. 120 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 2951 rpm Rated flow: 64 m³/h Rated head: 108.5 m Pump orientation: Vertical Shaft seal arrangement: Single Code for shaft seal: HQQE Approvals on nameplate: CE,EAC,UKCA,WRAS,ACS Curve tolerance: ISO9906:2012 3B Materials: Base: Stainless steel EN 1.4408 AISI 316 Impeller: Stainless steel EN 1.4401 AISI 316 Bearing: SIC Support bearing: Graflon Installation: Maximum ambient temperature: 55 °C Maximum operating pressure: 16 bar Max pressure at stated temp: 16 bar / 120 °C 16 bar / -40 °C

Qty.	Description
	Type of connection: DIN Size of inlet connection: DN 100 Size of outlet connection: DN 100 Pressure rating for connection: PN 16 Flange size for motor: FF350 Electrical data: Motor standard: IEC Motor type: SIEMENS IE Efficiency class: IE3 Rated power - P2: 30 kW Power (P2) required by pump: 30 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-420D/660-725Y V Rated current: 56,0-51,0/32,0-29,5 A Starting current: 660-660 % Cos phi - power factor: 0.86 Rated speed: 2955 rpm Efficiency: IE3 93,3% Motor efficiency at full load: 93.3-93.3 % Motor efficiency at 3/4 load: 93.6-93.6 % Motor efficiency at 1/2 load: 93.4-93.4 % Number of poles: 2 Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Motor No: 81U15332 Others: Minimum efficiency index, MEI ≥: 0.70 Net weight: 318 kg Gross weight: 356 kg Shipping volume: 0.805 m ³ Danish VVS No.: 385918051 Country of origin: DK Custom tariff no.: 84137075

96123786 CRN 64-5-1 A-F-A-E-HQQE 50 Hz




Description	Value		
General information:			
Product name:	CRN 64-5-1 A-F-A-E-HQQE		
Product No:	96123786		
EAN number:	5700396700472		
Technical:			
Pump speed on which pump data are based:	2951 rpm		
Rated flow:	64 m³/h		
Rated head:	108.5 m		
Maximum head:	139.2 m		
Stages:	5		
Impellers:	5		
Number of reduced-diameter impellers:	1		
Low NPSH:	N		
Pump orientation:	Vertical		
Shaft seal arrangement:	Single		
Code for shaft seal:	HQQE		
Approvals on nameplate:	CE,EAC,UKCA,WRAS,A CS		
Curve tolerance:	ISO9906:2012 3B		
Pump version:	A		
Model:	B		
Materials:			
Base:	Stainless steel		
Base:	EN 1.4408		
Base:	AISI 316		
Impeller:	Stainless steel		
Impeller:	EN 1.4401		
Impeller:	AISI 316		
Material code:	A		
Code for rubber:	E		
Bearing:	SIC		
Support bearing:	Graflon		
Installation:			
Maximum ambient temperature:	55 °C		
Maximum operating pressure:	16 bar		
Max pressure at stated temp:	16 bar / 120 °C		
Max pressure at stated temp:	16 bar / -40 °C		
Type of connection:	DIN		
Size of inlet connection:	DN 100		
Size of outlet connection:	DN 100		
Pressure rating for connection:	PN 16		
Flange size for motor:	FF350		
Connect code:	F		
Liquid:			
Pumped liquid:	Water		
Liquid temperature range:	-40 .. 120 °C		
Selected liquid temperature:	20 °C		
Density:	998.2 kg/m³		
Electrical data:			
Motor standard:	IEC		
Motor type:	SIEMENS		
IE Efficiency class:	IE3		
Rated power - P2:	30 kW		
Power (P2) required by pump:	30 kW		
Mains frequency:	50 Hz		
Rated voltage:	3 x 380-420D/660-725Y V		
Rated current:	56,0-51,0/32,0-29,5 A		
Starting current:	660-660 %		
Cos phi - power factor:	0.86		
Rated speed:	2955 rpm		
Efficiency:	IE3 93,3%		
Motor efficiency at full load:	93.3-93.3 %		



Description	Value
Motor efficiency at 3/4 load:	93.6-93.6 %
Motor efficiency at 1/2 load:	93.4-93.4 %
Number of poles:	2
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	81U15332
Controls:	
Frequency converter:	NONE
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	318 kg
Gross weight:	356 kg
Shipping volume:	0.805 m ³
Danish VVS No.:	385918051
Country of origin:	DK
Custom tariff no.:	84137075

96123786 CRN 64-5-1 A-F-A-E-HQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Spare parts CRN 64-5-1, Product No. 96123786
Produced After 1410 (production year and week number)

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
-	Base			96587697	1	pcs
6	Base				1	
- 80	Chamber stack			96416338	1	pcs
80	Chamber stack				1	
-	Kit, chambers			98634056	1	pcs
- 4a	Intermediate chamber cpl.				1	
	Guide cup				1	
	Guide cup				1	
	Cone				1	
	Guide vane				10	
	Chamber				1	
	Chamber				1	
45a	Neck ring cpl.				1	
47	Bearing				1	
- 47a	Bearing cpl.				1	
	Driver				1	
	Holder				1	
	Disc spring				1	
	Bearing ring				1	
-	Kit, coupling			96416594	1	pcs
	Adjusting fork				1	
- 8	Coupling cpl.		Dimension: 22/55		1	
9	Hex socket head cap screw		Designation: DIN 912		4	
			Length (mm): 25			
			Thread: M10			
10a	Coupling half				2	
-	Kit, coupling guard			96505135	1	pcs
7a	Socket button head screw				4	
7	Coupling guard				2	
-	Kit, cover			98832448	1	pcs
58a	Hex socket head cap screw		Designation: DIN 912		4	
			Length (mm): 25			
			Thread: M10			
58	Cover				1	
-	Kit, gaskets			96416599	1	pcs
	Adjusting fork				1	
37	O-ring				2	
38	O-ring				2	
38	O-ring				4	
60	Spring				4	
109	O-ring				1	
110	O-ring		Diameter: 21,2		1	
			Material type: EPDM			
			Thickness: 3,55			
-	Kit, impeller			98634079	1	pcs
48	Nut				1	
48	Nut				1	
49b	Split cone				1	
- 49	Impeller				1	
	Impeller hub				1	
49c	Wear ring				1	
-	Kit, Impeller, reduced			98634093	1	pcs
48	Nut				1	
48	Nut				1	
49b	Split cone				1	
- 49a	Impeller				1	
	Impeller hub				1	
49c	Wear ring				1	
-	Kit, plug			96505136	1	pcs

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
- 18	Air vent screw				1	
	Spindle				1	
	Plug				1	
25	Plug				4	
25	Plug				1	
38	O-ring				2	
38	O-ring				4	
38	O-ring		Diameter: 16,3		2	
			Material type: FKM			
			Thickness: 2,4			
38	O-ring		Diameter: 16,3		4	
			Material type: FKM			
			Thickness: 2,4			
38	O-ring		Diameter: 16,3		6	
			Material type: FKM			
			Thickness: 2,4			
-	Kit, shaft seal HQQE			96525458	1	pcs
	Grinding device				1	
- 105	Shaft seal		Material type: HQQE		1	
	Adjusting fork				1	
109	O-ring				1	
110	O-ring		Diameter: 21,5		1	
			Material type: EPDM			
			Thickness: 4,25			
-	Kit, wear parts			98497495	1	pcs
45	Seal ring				8	
47d	Lock ring				8	
47c	Bush				6	
49c	Wear ring				8	
65	Top f/neck ring				8	
-	Motor			99759457	1	pcs
156	Kit, fan			98062265	1	
151	Kit, fan cover			98062275	1	
156b	Kit, flange			98062279	1	
	Kit, lubrication nipple			98062531	1	
156a	Kit, ND-end shield cpl.			98062517	1	
159b	Kit, seal ring			98062551	1	
176	Kit, terminal board			98062236	1	
164a	Kit, terminal box			98062262	1	
1a	Motor stool			98967671	1	pcs
2	Pump head			96587726	1	pcs
7a	Socket button head screw			96549696	4	pcs
7	Coupling guard			96603279	2	pcs
9	Hex socket head cap screw		Designation: DIN 912	99789390	4	pcs
			Length (mm): 25			
			Thread: M10			
+ 18	Air vent screw			96547461	1	pcs
+ 18	Air vent screw			95061351	1	pcs
25	Plug			96536013	1	pcs
26	Staybolt		Length (mm): 643	98976743	4	pcs
			Thread: M16			
28	Hex socket head cap screw		Designation: DIN 912	96536147	4	pcs
			Length (mm): 50			
			Thread: M10			
28	Hex head screw			99869043	2	pcs
28	Hex head screw		Length (mm): 60	97506949	2	pcs
			Thread: M16			
32	Washer		Designation: DIN 125 A2	99944260	4	pcs
			Internal diameter: 17			
			Outer diameter: 30			
			Thickness: 3			
32	Washer		Designation: DIN 125 A	98923051	8	pcs
			Internal diameter: 17			
			Outer diameter: 30			

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
			Thickness: 3			
36	Nut		Thread: M16	99944257	4	pcs
36	Hex nut		Thread: M16	96620480	4	pcs
37	O-ring			96536142	1	pcs
37	O-ring		Diameter: 216	96536144	1	pcs
			Material type: FKM			
			Thickness: 4			
38	O-ring			99198815	4	pcs
38	O-ring		Diameter: 16,3	99198813	2	pcs
			Material type: FKM			
			Thickness: 2,4			
38	O-ring			99412727	4	pcs
38	O-ring		Diameter: 16,3	99412883	2	pcs
			Material type: FKM			
			Thickness: 2,4			
55	Outer sleeve			98820385	1	pcs
58	Cover			98893158	1	pcs
60	Spring			96536032	4	pcs
- 105	Shaft seal		Material type: HQQE	96984086	1	pcs
	Adjusting fork			96587896	1	
109	O-ring			99651108	1	
109	O-ring			96547586	1	
+ 105	Shaft seal		Material type: HQQE	96984070	1	pcs
440b	Lock ring			96547435	1	pcs