

Inventflow: Grundfos A-partner

Grundfos NBE 150-250/226-214 EUP AF1ABQQE

Find the pump here:

<https://inventflow.nl/en/pompenfilter/nbe/grundfos-nbe-150-250-226-214-eup-af1abqqe>

Contact

info@inventflow.nl

+31 (0) 546 45 80 72

Datasheet




Qty.	Description
1	NBE 150-250/226-214 EUP AF1ABQQE  Note! Product picture may differ from actual product Product No.: 98975359 Non-self priming, single-stage centrifugal Flange standard: pump according to EN 1092-2. The pump is for the pumping of thin, clean or slightly contaminated liquids without abrasive or long-fibred solids. The impeller is hydraulically as well as dynamically balanced. The pump has the following characteristics: - flange dimensions according to EN 1092-2, Pump housing: - Cast iron volute pump housing, - stainless steel shaft Impeller: and Cast iron impeller and bronze wear rings, - unbalanced mechanical shaft seal according to EN 12756. The pump is fitted with an IEC-flanged three-phase MGE motor with frequency converter and PI-controller integrated in the motor terminal box. No additional motor protection is required, as both motor and electronics are protected by integrated overload and temperature protection. An external sensor can be connected if controlled pump operation based on for example flow, differential pressure or temperature is required. A control panel enables setting of required setpoint as well as setting of pump to MIN or MAX operation or to STOP. The control panel has indicator lights for "Operation" and "Fault". Communication with the pump is possible by means of Grundfos R100 Remote Control enabling further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box holds terminals for the connection of: - pump start/stop (potential-free contact), - external remote setpoint setting via analog signal, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA, - 5 V voltage supply for setpoint potentiometer, I_{max} = 5 mA, - sensor, 0 - 5 V, 0 - 10 V, 0(4) - 20 mA,


Qty.	Description
	- 24 V voltage supply for sensor, I_{max} = 40 mA, - input for forced control to MIN or MAX (potential-free contact), - potential-free fault signal relay with changeover contact, - RS485 GENIbus. Controls: Frequency converter: Built-in Pressure sensor: N Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 120 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 1460 rpm Rated flow: 372.7 m³/h Rated head: 10.04 m Actual impeller diameter: 220 mm Nominal impeller diameter: 250 Shaft seal arrangement: Single Code for shaft seal: BQQE Curve tolerance: ISO9906:2012 3B Bearing design: Standard Materials: Pump housing: Cast iron EN-GJL-250 ASTM class 35 Wear ring: Brass Impeller: Cast iron EN-GJL-200 ASTM class 30 Shaft: Stainless steel EN 1.4301 AISI 304 Internal pump house coating: CED Installation: Maximum ambient temperature: 40 °C Maximum operating pressure: 10 bar Pipe connection standard: EN 1092-2 Size of inlet connection: DN 200 Size of outlet connection: DN 150 Pressure rating for connection: PN 10 Bearing lubrication: Grease Pump housing with feet: Yes Support block: N Electrical data: IE Efficiency class: IE3 Rated power - P₂: 15 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-480 V Rated current: 29.0-25.4 A Cos phi - power factor: 0.86-0.85 Rated speed: 240-1750 rpm Efficiency: IE3 92,1% Motor efficiency at full load: 92.1 % Number of poles: 4 Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F

Qty.	Description
	Motor No: 86906101 Others: Minimum efficiency index, MEI ≥: 0.68 Net weight: 330 kg Gross weight: 363 kg Shipping volume: 0.951 m³ Country of origin: HU Custom tariff no.: 84137051

98975359 NBE 150-250/226-214 EUP AF1ABQQE 50 Hz




Description	Value
General information:	
Product name:	NBE 150-250/226-214 EUP AF1ABQQE
Product No:	98975359
EAN number:	5712604540947
Technical:	
Pump speed on which pump data are based:	1460 rpm
Rated flow:	372.7 m³/h
Rated head:	10.04 m
Actual impeller diameter:	220 mm
Nominal impeller diameter:	250
Shaft seal arrangement:	Single
Shaft diameter:	42 mm
Code for shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Bearing design:	Standard
Materials:	
Pump housing:	Cast iron
Pump housing:	EN-GJL-250
Pump housing:	ASTM class 35
Wear ring:	Brass
Impeller:	Cast iron
Impeller:	EN-GJL-200
Impeller:	ASTM class 30
Shaft:	Stainless steel
Shaft:	EN 1.4301
Shaft:	AISI 304
Internal pump house coating:	CED
Material code:	A
Code for rubber:	E
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	10 bar
Pipe connection standard:	EN 1092-2
Size of inlet connection:	DN 200
Size of outlet connection:	DN 150
Pressure rating for connection:	PN 10
Bearing lubrication:	Grease
Pump housing with feet:	Yes
Support block:	N
Connect code:	F1
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
IE Efficiency class:	IE3
Rated power - P2:	15 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-480 V
Rated current:	29.0-25.4 A
Cos phi - power factor:	0.86-0.85
Rated speed:	240-1750 rpm
Efficiency:	IE3 92,1%
Motor efficiency at full load:	92.1 %
Number of poles:	4
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	YES
Motor No:	86906101
Mount. design. acc. IEC 34-7:	IM B35




Description	Value
Controls:	
Control panel:	Standard
Function Module:	PUMP I/O
Frequency converter:	Built-in
Pressure sensor:	N
Others:	
Minimum efficiency index, MEI ≥:	0.68
Net weight:	330 kg
Gross weight:	363 kg
Shipping volume:	0.951 m³
Country of origin:	HU
Custom tariff no.:	84137051

98975359 NBE 150-250/226-214 EUP AF1ABQQE 50 Hz



98975359 NBE 150-250/226-214 EUP AF1ABQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Spare parts NBE 150-250/226-214 EUP, Product No. 98975359
Produced After 2101 (production year and week number)

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
-	Bulk, Nut			92514632	1	pcs
67	Nut		Thread: M24		5	
-	Bulk, o-ring			92547634	1	pcs
72.a	O-ring		Diameter: 278,99		5	
			Material type: EPDM			
			Thickness: 3,53			
-	Bulk, Plug vent			96620482	1	pcs
18	Plug				5	
-	Bulk, Shaft seal			92514334	1	pcs
105	Shaft seal				5	
-	Kit, coupling guard			96809945	1	pcs
7a	Pan head screw				4	
7	Coupling guard				2	
-	Kit, cover			98990972	1	pcs
18	Plug				1	
36	Nut		Thread: M12		10	
77	Cover				1	
-	Kit, motor stool			96935191	1	pcs
1.a	Motor stool				1	
7	Coupling guard				2	
28	Hex head screw				4	
36	Hex nut		Thread: M16		8	
36	Nut		Thread: M12		10	
76a	Rivet				2	
77a	Pan head screw				4	
-	Kit, nut			96939132	1	pcs
11	Key				1	
-	36	Nut			1	
66a	Spring lock washer				1	
66	Washer				1	
67	Nut		Thread: M24		1	
-	Kit, pump housing			98801847	1	pcs
6	Pump housing				1	
20	Plug				2	
36	Nut		Thread: M12		10	
-	Kit, stub shaft			99248520	1	pcs
9	Socket set screw		Length (mm): 10		2	
			Thread: M8			
11	Key				1	
51	Stub shaft				1	
66a	Spring lock washer				1	
66	Washer				1	
67	Nut		Thread: M25		1	
-	Spare, O-ring			97757673	1	pcs
72.a	O-ring		Diameter: 278,99		1	
			Material type: EPDM			
			Thickness: 3,53			
-	Spare, plug vent			98164277	1	pcs
18	Plug				1	
-	Spare, shaft seal			98434909	1	pcs
105	Shaft seal				1	
-	Spare, wear ring			99208792	1	pcs
45	Wear ring				1	
-	Motor				1	pcs
-	Kit, bearing cpl.			96796674	1	
32b	Waved washer				1	
111	Ball bearing				1	
154	Ball bearing				1	
157	O-ring				1	

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
-	Kit, bearing plate			96796664	1	
155.a	Bearing cover				1	
208a	Gasket				3	
208	Hex socket head cap screw		Designation: DIN912		3	
			Length (mm): 40			
			Thread: M5			
-	Kit, connector plugs			96348923	1	
	Connector plug 5-pole				1	
	Connector plug 4-pole				1	
	Connector plug 4-pole				1	
	Connector plug 3-pole				1	
	Connector plug 3-pole				1	
	Connector plug 3-pole				1	
	Connector plug 3-pole				1	
	Connector plug				1	
- 273	Kit, control board			96348918	1	
	Service kit instruction				1	
	Controlboard				1	
-	Kit, eyebolt			96796712	1	
189	Eyebolt				2	
-	Kit, fan cover			96830826	1	
151	Fan cover				1	
152.a	Rubber bush				4	
152	Hex head cap screw				4	
196	Diaphragm				1	
-	Kit, flange			97899854	1	
156.b	Flange				1	
159.b	Seal ring				1	
185.b	Nut				4	
185	Hex socket head cap screw				4	
186	Drain plug				4	
195.a	Grease nipple				1	
-	Kit, foot			96796665	1	
191	Foot				2	
192	Hex socket head cap screw				4	
194	Lock washer				4	
194	Nut				4	
-	Kit, funct. module - E-pump			96348929	1	
263	MGE large I/O add-on				1	
-	Kit, funct. module -Geni/RS485			96348932	1	
263	Add-on module, cpl. w/plugs				1	
-	Kit, gaskets			96798508	1	
184	O-ring		Diameter: 235		2	
275	Kit, inverter board			96348920	1	
-	Kit, key			96279873	1	
40	Parallel key		Designation: DS96 DIN 6885		1	
			Dimension: 12X8X90			
-	Kit, lubrication nipple			96796671	1	
195.b	Grease nipple				2	
195.a	Grease nipple				1	
-	Kit, motor			96844400	1	
	Flex insulation				3	
	EMC filter				1	
	Cover cpl.				1	
	Fan				1	
	Motor				1	
99a	Retaining ring				1	

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aantal	Eenheid
151	Fan cover				1	
152.a	Rubber bush				4	
152	Hex head cap screw				4	
177	Torx Screw				1	
185.b	Nut				4	
185.b	Nut				4	
191	Foot				2	
192	Hex socket head cap screw				4	
194	Lock washer				4	
196	Diaphragm				1	
273a	Pan head thread forming screw				4	
-	Kit, ND-end shield cpl.			96796669	1	
32b	Waved washer				1	
156.a	End shield NDE				1	
157	O-ring				1	
159	V-ring				1	
185.c	Nut				4	
185.a	Hex socket head cap screw				4	
195.b	Grease nipple				1	
-	Kit, opr. panel			96348924	1	
259	Operation panel				1	
274	Kit, rectifier board			96348921	1	
-	Kit, terminal box			96348914	1	
164	Cover cpl.				1	
166	Pan head thread forming screw				5	
251	Terminal box				1	
277	Blind cover				1	
283	Motor cover cpl.				1	
284	Cover				1	
-	Kit, varistor			96348917	1	
279.b	Pan head thread forming screw				2	
279	Varistor				1	
49	Impeller			99370978	1	pcs