

Inventflow: Grundfos A-partner

Grundfos NB 100-160/167 EUP AF2ABQQE

Find the pump here:

<https://inventflow.nl/en/pompenfilter/nb/grundfos-nb-100-160-167-eup-af2abqqe>


Contact

info@inventflow.nl

+31 (0) 546 45 80 72


Datasheet




Qty.	Description
1	NB 100-160/167 EUP AF2ABQQE  Product No.: 98975472 Non-self priming, single-stage centrifugal Flange standard: pump according to EN 1092-2. The pump is for the pumping of thin, clean or slightly contaminated liquids without abrasive or long-fibred solids. The pump is directly coupled with an Phase: IEC-flanged 3-phase AC motor. The impeller is hydraulically as well as dynamically balanced. The pump has the following characteristics: - flange dimensions according to EN 1092-2, Pump housing: - Cast iron volute pump housing, - stainless steel shaft Impeller: and Cast iron impeller and bronze wear rings, - unbalanced mechanical shaft seal according to EN 12756. Controls: Frequency converter: NONE Pressure sensor: N Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 120 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 2950 rpm Rated flow: 227.9 m³/h Rated head: 26.18 m Actual impeller diameter: 167 mm Nominal impeller diameter: 160 Shaft seal arrangement: Single Code for shaft seal: BQQE Curve tolerance: ISO9906:2012 3B Bearing design: Standard Materials: Pump housing: Cast iron EN-GJL-250 ASTM class 35 Wear ring: Brass Impeller: Cast iron

Qty.	Description
	EN-GJL-200 ASTM class 30 Shaft: Stainless steel EN 1.4301 AISI 304 Internal pump house coating: CED Installation: Maximum ambient temperature: 60 °C Maximum operating pressure: 16 bar Pipe connection standard: EN 1092-2 Size of inlet connection: DN 125 Size of outlet connection: DN 100 Pressure rating for connection: PN 16 Bearing lubrication: Grease Pump housing with feet: Yes Support block: N Electrical data: Motor type: 180MB IE Efficiency class: IE3 Rated power - P2: 22 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-415D/660-690Y V Rated current: 39.5/22.8 A Starting current: 830 % Cos phi - power factor: 0.90-0.90 Rated speed: 2950 rpm Efficiency: IE3 92,7% Motor efficiency at full load: 92.7 % Motor efficiency at 3/4 load: 93.7 % Motor efficiency at 1/2 load: 94.4 % Number of poles: 2 Enclosure class (IEC 34-5): 55 Dust/Jetting Insulation class (IEC 85): F Motor No: 87470023 Others: Minimum efficiency index, MEI ≥: 0.70 Net weight: 206 kg Gross weight: 231 kg Shipping volume: 0.707 m³ Country of origin: HU Custom tariff no.: 84137051

98975472 NB 100-160/167 EUP AF2ABQQE 50 Hz




Description	Value
General information:	
Product name:	NB 100-160/167 EUP AF2ABQQE
Product No:	98975472
EAN number:	5712604543054
Technical:	
Pump speed on which pump data are based:	2950 rpm
Rated flow:	227.9 m³/h
Rated head:	26.18 m
Actual impeller diameter:	167 mm
Nominal impeller diameter:	160
Shaft seal arrangement:	Single
Shaft diameter:	24 mm
Code for shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Bearing design:	Standard
Materials:	
Pump housing:	Cast iron
Pump housing:	EN-GJL-250
Pump housing:	ASTM class 35
Wear ring:	Brass
Impeller:	Cast iron
Impeller:	EN-GJL-200
Impeller:	ASTM class 30
Shaft:	Stainless steel
Shaft:	EN 1.4301
Shaft:	AISI 304
Internal pump house coating:	CED
Material code:	A
Code for rubber:	E
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	16 bar
Pipe connection standard:	EN 1092-2
Size of inlet connection:	DN 125
Size of outlet connection:	DN 100
Pressure rating for connection:	PN 16
Bearing lubrication:	Grease
Pump housing with feet:	Yes
Support block:	N
Connect code:	F2
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	180MB
IE Efficiency class:	IE3
Rated power - P2:	22 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415D/660-690Y V
Rated current:	39.5/22.8 A
Starting current:	830 %
Cos phi - power factor:	0.90-0.90
Rated speed:	2950 rpm
Efficiency:	IE3 92,7%
Motor efficiency at full load:	92.7 %
Motor efficiency at 3/4 load:	93.7 %
Motor efficiency at 1/2 load:	94.4 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting




Description	Value
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	87470023
Mount. design. acc. IEC 34-7:	IM B35
Controls:	
Frequency converter:	NONE
Pressure sensor:	N
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	206 kg
Gross weight:	231 kg
Shipping volume:	0.707 m ³
Country of origin:	HU
Custom tariff no.:	84137051

98975472 NB 100-160/167 EUP AF2ABQQE 50 Hz



98975472 NB 100-160/167 EUP AF2ABQQE 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Spare parts NB 100-160/167 EUP, Product No. 98975472
Produced After 2101 (production year and week number)

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aanta	Eenhei
	Bulk, Nut			92514630	1	pcs
67	Nut		Thread: M14		5	
	Bulk, o-ring			92547662	1	pcs
72a	O-ring				5	
	Bulk, Plug vent			96620482	1	pcs
18	Plug				5	
	Bulk, Shaft seal			99380916	1	pcs
105	Shaft seal				5	
	Kit, coupling guard			96809946	1	pcs
7a	Pan head screw				4	
7	Coupling guard				2	
	Kit, motor stool			98990921	1	pcs
1a	Motor stool				1	
7	Coupling guard				2	
18	Plug				1	
28	Hex head screw				4	
36	Hex nut		Thread: M16		4	
36	Nut		Thread: M10		6	
76a	Rivet				2	
77a	Pan head screw				4	
	Kit, nut			96939128	1	pcs
11	Parallel key		Dimension: 6X6X35		1	
36	Nut				1	
66a	Spring lock washer				1	
66	Washer				1	
67	Nut		Thread: M14		1	
	Kit, pump housing			98776475	1	pcs
6	Pump housing				1	
20	Plug				2	
36	Nut		Thread: M10		6	
	Kit, stub shaft			96039355	1	pcs
9	Socket set screw		Length (mm): 10		2	
			Thread: M8			
11	Parallel key		Dimension: 6X6X35		1	
51	Stub shaft				1	
66a	Spring lock washer				1	
66	Washer				1	
67	Nut		Thread: M14		1	
	Spare, O-ring			97757659	1	pcs
72a	O-ring				1	
	Spare, plug vent			98164277	1	pcs
18	Plug				1	
	Spare, shaft seal			98434904	1	pcs
105	Shaft seal				1	
	Spare, wear ring			99208748	1	pcs
45	Wear ring				1	
	Motor				1	pcs
	Kit, bearing cpl.		Designation: 6310.Z.C4-6310.Z.C4	96796811	1	
111	Ball bearing				1	
154	Ball bearing				1	
158	Waved washer				1	
	Kit, bearing plate			96796809	1	
155. a	Cover				1	
208a	Gasket				3	
208	Hex socket head cap screw		Designation: DIN912		3	
			Length (mm): 40			

Pos	Omschrijving	Opmerking tekst	Classificatie Gegevens	Onderdeelnr.	Aanta	Eenhei
			Thread: M5			
	Kit, eyebolt			96796712	1	
189	Eyebolt				2	
	Kit, fan			96796652	1	
156. c	Retaining ring				1	
156	Fan				1	
	Kit, fan cover			96796647	1	
151	Fan cover				1	
152. a	Rubber bush				4	
152	Hex head cap screw				4	
196	Diaphragm				1	
	Kit, flange			96796807	1	
156. b	Flange				1	
159. b	Seal ring				1	
185	Hex socket head cap screw				4	
186	Drain plug				4	
195. a	Grease nipple				1	
	Kit, foot			96796804	1	
191. a	Foot				1	
191	Foot				1	
192	Hex socket head cap screw				4	
194	Lock washer				4	
194	Nut				4	
	Kit, gaskets			96798508	1	
184	O-ring		Diameter: 235		2	
	Kit, key			96796817	1	
171	Parallel key				1	
	Kit, lubrication nipple			96796671	1	
195. b	Grease nipple				2	
195. a	Grease nipple				1	
	Kit, ND-end shield cpl.			96796810	1	
156a	End shield NDE				1	
158	Waved washer				1	
159	V-ring				1	
185. c	Nut				4	
185. a	Hex socket head cap screw				4	
195. b	Grease nipple				1	
	Kit, shaft seal			96843460	1	
159. b	V-ring				1	
159	V-ring				1	
	Kit, terminal board			96796657	1	
	Terminal connection				3	
	Washer				12	
36	Hex nut				12	
173	Torx Screw				1	
176. d	Terminal board				1	
176	Terminal board				1	
177	Torx Screw				1	
	Kit, terminal box cover			96796659	1	
164	Terminal box cover				1	
273a	Pan head thread forming screw				4	
49	Impeller			92538629	1	pcs